

Order Information

(Please fill in the blanks while placing the order)

Note: 24VDC Chassis should be working with 24VDC version modules only, and 48VDC chassis should be working with 48VDC version modules only.

		C	P	G	S1	S2	S3	S4	S5	S6
	SICOM4000									
Material No.	Chassis									
3.01.80.0001-0	SICOM4000-MB-24VDC, SICOM4000 Chassis 24VDC Version	MB24								
3.01.80.0002-0	SICOM4000-MB-48VDC, SICOM4000 Chassis 48VDC Version	MB48								
	Power Supply Module									
3.01.80.0020-0	SM4.1-Power-24VDC, 24VDC(18-36VDC) power supply module		24DC							
3.01.80.0021-0	SM4.1-Power-48VDC, 48VDC(36-72VDC) power supply module		48DC							
	Gigabit Module									
	None			XX						
3.01.80.0022-0	SM4.1-4GX-24VDC, interface module with 4 Gigabit SFP ports 24VDC version			4GX24						
3.01.80.0043-0	SM4.1-4GX-48VDC, interface module with 4 Gigabit SFP ports 48VDC version			4GX48						
3.01.80.0023-0	SM4.1-4GE-24VDC, interface module with 4 10/100/1000Base-TX RJ45 ports 24VDC version			4GE24						
3.01.80.0042-0	SM4.1-4GE-48VDC, interface module with 4 10/100/1000Base-TX RJ45 ports 48VDC version			4GE48						
	S1-S6 100M Modules									
	None							XX		
3.01.80.0024-0	SM4.1-4T-24VDC, interface module with 4 10/100Base-TX RJ45 ports, 24VDC version							4T24		
3.01.80.0044-0	SM4.1-4T-48VDC, interface module with 4 10/100Base-TX RJ45 ports, 48VDC version							4T48		
3.01.80.0019-0	SM4.1-4D-232/485-24VDC, interface module with 4 RS232/485 serial ports, 24VDC version							4D24		
3.01.80.0041-0	SM4.1-4D-232/485-48VDC, interface module with 4 RS232/485 serial ports, 48VDC version							4D48		
3.01.80.0003-0	SM4.1-4S-SC-1310-40-24VDC, interface module with 4 100Base-FX single mode fiber ports, 1310nm 40km, SC connector, 24VDC version							4SSC24		
3.01.80.0005-0	SM4.1-4S-ST-1310-40-24VDC, interface module with 4 100Base-FX single mode fiber ports, 1310nm 40km, ST connector, 24VDC version							4SST24		
3.01.80.0004-0	SM4.1-4S-FC-1310-40-24VDC, interface module with 4 100Base-FX single mode fiber ports, 1310nm 40km, FC connector, 24VDC version							4SFC24		
3.01.80.0009-0	SM4.1-4S-SC-1310-60-24VDC, interface module with 4 100Base-FX single mode fiber ports, 1310nm 60km, SC connector, 24VDC version							4SSC6024		
3.01.80.0010-0	SM4.1-4S-SC-1550-80-24VDC, interface module with 4 100Base-FX single mode fiber ports, 1550nm 80km, SC connector, 24VDC version							4SSC8024		
3.01.80.0006-0	SM4.1-4M-SC-1310-5-24VDC, interface module with 4 100Base-FX multi mode fiber ports, 1310nm 5km, SC connector, 24VDC version							4MSC24		
3.01.80.0008-0	SM4.1-4M-ST-1310-5-24VDC, interface module with 4 100Base-FX multi mode fiber ports, 1310nm 5km, ST connector, 24VDC version							4MST24		
3.01.80.0007-0	SM4.1-4M-FC-1310-5-24VDC, interface module with 4 100Base-FX multi mode fiber ports, 1310nm 5km, FC connector, 24VDC version							4MFC24		
3.01.80.0025-0	SM4.1-4S-SC-1310-40-48VDC, interface module with 4 100Base-FX single mode fiber ports, 1310nm 40km, SC connector, 48VDC version							4SSC48		
3.01.80.0027-0	SM4.1-4S-ST-1310-40-48VDC, interface module with 4 100Base-FX single mode fiber ports, 1310nm 40km, ST connector, 48VDC version							4SST48		
3.01.80.0026-0	SM4.1-4S-FC-1310-40-48VDC, interface module with 4 100Base-FX single mode fiber ports, 1310nm 40km, FC connector, 48VDC version							4SFC48		
3.01.80.0031-0	SM4.1-4S-SC-1310-60-48VDC, interface module with 4 100Base-FX single mode fiber ports, 1310nm 60km, SC connector, 48VDC version							4SSC6048		
3.01.80.0032-0	SM4.1-4S-SC-1550-80-48VDC, interface module with 4 100Base-FX single mode fiber ports, 1550nm 80km, SC connector, 48VDC version							4SSC8048		
3.01.80.0028-0	SM4.1-4M-SC-1310-5-48VDC, interface module with 4 100Base-FX multi mode fiber ports, 1310nm 5km, SC connector, 48VDC version							4MSC48		
3.01.80.0030-0	SM4.1-4M-ST-1310-5-48VDC, interface module with 4 100Base-FX multi mode fiber ports, 1310nm 5km, ST connector, 48VDC version							4MST48		
3.01.80.0029-0	SM4.1-4M-FC-1310-5-48VDC, interface module with 4 100Base-FX multi mode fiber ports, 1310nm 5km, FC connector, 48VDC version							4MFC48		
3.01.80.0011-0	SM4.1-2S-SC-1310-40-2T-24VDC, interface module with 2 100Base-FX single mode fiber ports, 1310nm 40km, SC connector, and 2 10/100Base-TX RJ45 ports, 24VDC version							2SSC2T24		
3.01.80.0013-0	SM4.1-2S-ST-1310-40-2T-24VDC, interface module with 2 100Base-FX single mode fiber ports, 1310nm 40km, ST connector, and 2 10/100Base-TX RJ45 ports, 24VDC version							2SST2T24		
3.01.80.0012-0	SM4.1-2S-FC-1310-40-2T-24VDC, interface module with 2 100Base-FX single mode fiber ports, 1310nm 40km, FC connector, and 2 10/100Base-TX RJ45 ports, 24VDC version							2SFC2T24		

3.01.80.0017-0	SM4.1-2S-SC-1310-60-2T-24VDC, interface module with 2 100Base-FX single mode fiber ports, 1310nm 60km, SC connector, and 2 10/100Base-TX RJ45 ports, 24VDC version	2SSC60T24
3.01.80.0018-0	SM4.1-2S-SC-1310-80-2T-24VDC, interface module with 2 100Base-FX single mode fiber ports, 1310nm 80km, SC connector, and 2 10/100Base-TX RJ45 ports, 24VDC version	2SSC80T24
3.01.80.0014-0	SM4.1-2M-SC-1310-5-2T-24VDC, interface module with 2 100Base-FX multi mode fiber ports, 1310nm 5km, SC connector, and 2 10/100Base-TX RJ45 ports, 24VDC version	2MSC2T24
3.01.80.0016-0	SM4.1-2M-ST-1310-5-2T-24VDC, interface module with 2 100Base-FX multi mode fiber ports, 1310nm 5km, ST connector, and 2 10/100Base-TX RJ45 ports, 24VDC version	2MST2T24
3.01.80.0015-0	SM4.1-2M-FC-1310-5-2T-24VDC, interface module with 2 100Base-FX multi mode fiber ports, 1310nm 5km, FC connector, and 2 10/100Base-TX RJ45 ports, 24VDC version	SMFC2T24
3.01.80.0033-0	SM4.1-2S-SC-1310-40-2T-48VDC, interface module with 2 100Base-FX single mode fiber ports, 1310nm 40km, SC connector, and 2 10/100Base-TX RJ45 ports, 48VDC version	2SSC2T48
3.01.80.0035-0	SM4.1-2S-ST-1310-40-2T-48VDC, interface module with 2 100Base-FX single mode fiber ports, 1310nm 40km, ST connector, and 2 10/100Base-TX RJ45 ports, 48VDC version	2SST2T48
3.01.80.0034-0	SM4.1-2S-FC-1310-40-2T-48VDC, interface module with 2 100Base-FX single mode fiber ports, 1310nm 40km, FC connector, and 2 10/100Base-TX RJ45 ports, 48VDC version	2SFC2T48
3.01.80.0039-0	SM4.1-2S-SC-1310-60-2T-48VDC, interface module with 2 100Base-FX single mode fiber ports, 1310nm 60km, SC connector, and 2 10/100Base-TX RJ45 ports, 48VDC version	2SSC60T48
3.01.80.0040-0	SM4.1-2S-SC-1310-80-2T-48VDC, interface module with 2 100Base-FX single mode fiber ports, 1310nm 80km, SC connector, and 2 10/100Base-TX RJ45 ports, 48VDC version	2SSC80T48
3.01.80.0036-0	SM4.1-2M-SC-1310-5-2T-48VDC, interface module with 2 100Base-FX multi mode fiber ports, 1310nm 5km, SC connector, and 2 10/100Base-TX RJ45 ports, 48VDC version	2MSC2T48
3.01.80.0038-0	SM4.1-2M-ST-1310-5-2T-48VDC, interface module with 2 100Base-FX multi mode fiber ports, 1310nm 5km, ST connector, and 2 10/100Base-TX RJ45 ports, 48VDC version	2MST2T48
3.01.80.0037-0	SM4.1-2M-FC-1310-5-2T-48VDC, interface module with 2 100Base-FX multi mode fiber ports, 1310nm 5km, FC connector, and 2 10/100Base-TX RJ45 ports, 48VDC version	SMFC2T48